
2023 Efficiency Requirements for 25C Tax Credits



Split Ducted Heat Pump Specifications - North Region				
SEER2	EER2 HSPF2 COP at 5°F*		COP at 5°F*	Capacity Ratio^
≥15.2	≥10.0	≥8.1	≥1.75	≥58% at 17°F/47°F or ≥70% at 5°F/47°F

Non-Ducted Heat Pump Specifications - North Region				
SEER2	SEER2 EER2 HSPF2 COP at 5°F*		Capacity Ratio^	
≥16.0	≥9.0	≥9.5	≥1.75	≥58% at 17°F/47°F or ≥70% at 5°F/47°F

Packaged Heat Pump Specifications - North Region				
SEER2	SEER2 EER2 HSPF2		COP at 5°F*	Capacity Ratio [^]
≥15.2	≥10.0	≥8. 1	≥1.75	≥58% at 17°F/47°F or ≥70% at 5°F/47°F

Split Ducted Heat Pump Specifications - South Region		
SEER2	EER2	HSPF2
≥ <mark>1</mark> 5.2	≥11.7	≥7.8

Non-Ducted Heat Pump Specifications - South Region		
SEER2	EER2	HSPF2
≥16.0	≥12.0	≥9.0

Packaged Heat Pump Specifications - South Region			
SEER2	EER2	HSPF2	
≥15.2	≥10.6	≥7.2	